

RC832S

5.8G High Sensitivity Receiver



RC832S

5.8G High Sensitivity Receiver

Technical specification

RC832S 5.8G High Sensitivity Receiver	Receiving Sensitivity	-95dBm
	Receiving Frequency	ISM 5.8GHz 32CH
	Power Supply Voltage	DC 7-12 V
	Supply Current	130mA
	RF input matching	50ohm SMA
	Video Output Level	1.0Vp_p 75Ω
	Audio Output Level	1.0Vp_p 10kΩ
	Dimension	80x54x15mm
	Weight	80g

Frequencies and Bands

CH FR	CH1	CH2	CH3	CH4	CH5	CH6	CH7	CH8
FR1 (A)	5865M	5845M	5825M	5805M	5785M	5765M	5745M	5725M
FR2 (B)	5733M	5752M	5771M	5790M	5809M	5828M	5847M	5866M
FR3 (E)	5705M	5685M	5665M	5645M	5885M	5905M	5925M	5945M
FR4 (F)	5740M	5760M	5780M	5800M	5820M	5840M	5860M	5880M
FR5 (H)	5658M	5695M	5732M	5769M	5806M	5843M	5880M	5917M
FR6 (L)	5362M	5399M	5436M	5473M	5510M	5547M	5584M	5621M